



EXPORT BARREL 300 LITRES -LTT-

THICKNESS BEFORE MACHINING	CAPACITY	WEIGHT	HOOPS	STAVE LENGTH	HEAD DIAMETER	BILGE DIAMETER
25-27 mm	300 litres	± 60 kg	6 galvanized	102 cm	62 cm	78 cm

Values are provided for guidance only; tolerances available upon request.



non-contractual photo

Wood specifications

Type:	Quercus sessilis, quercus robur
Origin:	Selection & assembly of numerous sources
Ageing:	Open air ageing from 20 to 24 months minimum
Quality control:	Test of no contaminating agents: TCA/Radioactivity

Manufacture specifications

Pre-toast:	Traditional wood fire
Toast:	Traditional wood fire - Precise intensity
Bung hole:	Burned or not - Diameter 45/56 mm
Bung:	Cork bung, wooden bung or silicon bung
Completion of heads:	Assembled with stainless pins marked with our mark+ identification
Esquive:	Optional
Toasted heads:	On request
Check watertightness:	Hot water pressure test – Our barrels are designed for use at pressures below 0.6 bar. Drained and dried without the addition of sulfur.
Packing:	Heavy shrink-wrapped plastic
Identification:	Single identification number
Guarantees:	100% PEFC ISO 9001 Bureau Veritas "Origine France Garantie" Certification Bureau Veritas issues a certificate for our HACCP mastery of Tonnellerie Leroi products N°BV/181/RE. 1 year material and workmanship Control of no contaminating agents. Tests carried out by the EXACT laboratory, accredited by COFRAC under N°1-2201 (scope available on www.cofrac.fr)



BVCert. 6091858

